

**First Exploration and Petroleum Development Company Limited
Operator of the NNPC/FIRST E&P Joint Venture**

Advert for Tender Opportunity

Hire of 300 Feet Jack-Up Drilling Rig for NNPC/First E&P JV Operations

(NipeX Tender No.4500001)

(1.0) Introduction

FIRST Exploration and Petroleum Development Company Limited, on behalf of NNPC/FIRST E&P Joint Venture, intends to hire a 300ft Jack Up Drilling Rig for the drilling and completion of 18 wells with anticipated starting date from the 3rd Quarter of 2016 for Two (2) years firm period plus one year optional extension.

FIRST E&P therefore uses this medium to inform suitable and reputable Companies having requisite experience and resources for the execution of a project of this magnitude to register or update their registration with NipeX for consideration in the subject opportunity

(2.0) Scope of Work/Service Requirement

The offshore drilling campaign is expected to commence from the 3rd Quarter of 2016 for at least a two (2) years duration, with a 1-year extension option. Interested bidders must be able to provide 300 feet Jack-up drilling rig with the following technical requirements and specifications at minimum:

- (a) Minimum Operating Water Depth: 60 feet
- (b) Maximum Operating Water Depth: 200 feet
- (c) Leg Length/Type: >400ft/Open Truss
- (d) Well Depth Rating: 20,000 feet
- (e) Draw works Capacity: 2,000 HP
- (f) Rotary Table: 1,000HP, 37.5" diameter
- (g) Derrick Load Capacity: 1,250Kips

- (h) Hook Load capacity: 1,000Kips
- (i) Variable Deck Load (VDL) Capacity: 3,500 Kips (j) Cantilever Envelope – Minimum; 40 X 24ft
- (k) Triplex Mud Pumps: Three (3) of 1600 HP each and 5,000 psi Stand Pipe Pressure
- (l) BOP system;
 - (i) 21-1/4" 2000 psi Working Pressure (Class IV)
 - (ii) 13-5/8" 10,000psi Working Pressure (Class IV)
 - (iii) Annular system, 13-5/8" 5,000psi Working Pressure
- (m) Diverter System;
 - (i) 29 1/2" 5000 psi
 - (ii) 21-1/4" 2000 psi
- (n) Double Studded Adapter (DSA): 13 5/8" x 11"
- (o) Total Mud tank capacity-3,000bbls
- (p) Top Drive System: TDS-4 or equivalent
- (q) Shale Shaker: Minimum 3 pcs Single
- (r) Centrifuge system(s): Fully variable speed centrifuges capable of processing 200gallons per minute of 10 ppg mud.
- (s) Cuttings Dryer Units: Capable of processing up to 30 tons per hour and reducing oil on cuttings to less than 5% measured by weight (wet)
- (t) Accommodation: 120-man bed space at the minimum
- (u) Compliance with DPR Zero Discharge for Hazardous Waste and as per Environmental Guidelines

- (v) Evidence of Contractor's current International Association of Drilling Contractor (IADC) registration
- (w) Evidence of current valid ABS
- (x) Rig shall be mobilized on first location in August 2016.

(3.0) Mandatory Requirements

- (a) To be eligible for this tender exercise, interested contractors are required to be pre-qualified in the 3.04.01- Drilling Rigs (Product/Services) in NipeX Joint Qualification System (NJQS) database. **All successfully pre-qualified Suppliers in this category will receive Invitation to Technical Tender (ITT).**
- (b) To determine if you are pre-qualified and view the product/service category you are listed for: Open www.nipexng.com and access NJQS with your log in details, click on continue Joint Qualification Scheme tool, click check my supplier status and then click supplier product group.
- (c) If you are not listed in a product/service category you are registered with DPR to do business, contact **NipeX office at 30, Oyinkan Abayomi Street, Ikoyi, Lagos** with your DPR certificate as evidence for verification and necessary update.
- (d) To initiate the JQS pre-qualification process, access www.nipexng.com to download the application form, make necessary payments and contact NipeX office for further action.
- (e) To be eligible, all tenders must comply with the Nigerian Content requirements in the NipeX system

(4.0) Nigerian Content

Bidders are invited to express complete understanding and willingness to develop in-country capability and cap